

MICROLENE water purifier

Phone: N.Z. 0800-654-333

F500

PEDESTAL DRINKING FOUNTAIN



F500

Model

- F500 is a non-refrigerated stainless steel drinking fountain plumbed through the cabinet base for complete concealment of plumbing lines.

Standard Features

- ▶ Waterways Are Lead-Free In Materials & Construction
- ▶ Removable Front Cabinet Panel For Easy Access To All Plumbing
- ▶ Deep Sump Receptor Minimizes Splashing
- ▶ Dial-A-Drink Bubbler
- ▶ Flexi-Guard Rubber Mouthguard On Bubbler
- ▶ Built-In Pressure Regulator Assures Smooth, Steady Water Flow
- ▶ Satin Finish Stainless Steel Surfaces
- ▶ Removable Chrome-Plated Brass Drain Strainer
- ▶ Limited 1-Year Warranty

Installation

- ▶ Prior to roughing-in, consult local, state and federal codes for proper mounting height
- ▶ Shipped with complete instructions

Colours

- Standard finish: Stainless Steel

Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.



Model covered by this specification complies with all known Plumbing Codes. Certified by Canadian Standards Association.

PHYSICAL DIMENSIONS in mm

MODEL	STYLE	HEIGHT OF CABINET	WIDTH	DEPTH	Extend From Wall	Net Wt. Approx.
F500	Pedestal	914	356	289	289	12.7kg

Specifications are subject to change without notice.

Drinking Fountain Model F500

Pedestal Drinking Fountain Specifications

DIMENSIONAL DRAWING	ROUGHING-IN DRAWING		
<p>Labels: $\frac{3}{8}$ NPT NIPPLE, END OF $\frac{1}{4}$ TAILPIECE, FLOOR LINE, FOUNTAIN</p>	<p>Labels: MOUNTING SCREW LOCATIONS (4), FRONT OF FOUNTAIN, $\frac{3}{8}$"(76) DIA HOLE IN BASE FOR WASTE CONNECTION, $\frac{1}{2}$"(38) DIA HOLE IN BASE FOR $\frac{3}{8}$ PIPE INLET WATER LINE</p>		
<p>NOTES:</p> <p>TRAP, OFFSET, FIXTURE STOP VALVE, AND UNION NOT FURNISHED WITH DRINKING FOUNTAIN.</p> <p>ALL DIMENSIONS ARE IN INCHES. DIMENSIONS IN PARENTHESES () ARE IN MILLIMETERS.</p>	<p>NOTES:</p> <p>MOUNTING HOLES IN BASE ARE OVERSIZE TO PROVIDE AMPLE CLEARANCE FOR $\frac{1}{4}$"(6) DIA FASTENERS. FLAT WASHERS SHOULD BE USED TO PROVIDE MAXIMUM STRENGTH.</p>		
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 60%; text-align: center;">029574-001</td> <td style="width: 40%; text-align: center;"> SCALE: NTS DRAWN: CAD DATE: 3.1.99 029574-001 ECN: 890248 ROUGHING-IN, B. DIM DWG CAB FTM </td> </tr> </table>		029574-001	SCALE: NTS DRAWN: CAD DATE: 3.1.99 029574-001 ECN: 890248 ROUGHING-IN, B. DIM DWG CAB FTM
029574-001	SCALE: NTS DRAWN: CAD DATE: 3.1.99 029574-001 ECN: 890248 ROUGHING-IN, B. DIM DWG CAB FTM		

Distributed by: **CONTAMINATION CONTROL LTD** P.O. Box 14-641, PANMURE, AUCKLAND 6, NZ PH: (09) 570 - 9135
 46 Lunn Ave, MT. Wellington FAX: (0064) (09) 527 - 7654